## CONE CRUSHER TECHNICAL DETAILS

| CONE CRUSHER | | Power (H. P.) | Nominal Feed Opening in mm | CAPACITY IN TPH AT CLOSE SIDE SETTING IN mm | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Model | | | | 10 | 13 | 16 | 19 | 22 | 25 | 32 | 38 |
| C-800 | 0880 | 75-100 | 80 | 30-50 | 35-60 | 50-70 | 55-80 | | | | |
| | 1280 | | 110 | 35-60 | 40-65 | 50-80 | 60-90 | 65-95 | 80-120 | | |
| | 1680 | | 140 | | | 50-85 | 75-100 | 80-110 | 100-140 | 115-150 | |
| C-1000 | 12100 | 125-175 | 100 | 50-80 | 60-90 | 75-110 | 85-130 | 100-135 | 110-140 | | |
| | 16100 | | 150 | | 80-110 | 80-120 | 100-135 | 110-150 | 130-160 | 170-190 | |
| | 20100 | | 190 | | | 90-140 | 110-160 | 140-180 | 170-210 | 200-240 | 210-240 |
| C-1200 | 16120 | 175-250 | 125 | | 90-130 | 95-145 | 100-150 | 110-160 | 125-170 | | |
| | 20120 | | 180 | | | 140-180 | 160-200 | 180-215 | 190-230 | 210-250 | 220-270 |
| | 24120 | | 225 | | | | 170-210 | 190-230 | 220-250 | 240-270 | 260-300 |

**Capacities indicated are based on feed material weighting 1.6 T/m$^3$, under ideal conditions of feed, grading, moisture content etc.**

(Specifications are subject to change without notice.)


**SHREE CONMIX ENGINEERS PVT. LTD.**

7603, G.I.D.C. Estate, Phase-IV, Vatva, Ahmedabad - 382 445.
Phone : 0091 - 79 - 2584 0917, Telefax : 0091 - 79 - 2584 0297
E-mail : info@conmixcrusher.com Website : www.conmixcrusher.com


HATVEE / 10-05 / Ph.-079 2755 1570