



## JAW CRUSHER CAPACITY IN TPH

CSS	50	60	70	80	90	100	125	150	175	200	250
20" x 32"	40	50	70	85	100	110	130	160			
	60	70	90	100	125	130	160	220			
24" x 36"		80	100	120	140	160	180	230	280		
		100	120	140	170	180	230	280	340		
30" x 40"		100	130	150	170	180	200	240	290	350	
		130	160	180	200	215	260	300	360	400	
34" x 44"			160	180	210	240	280	320	360	420	
			190	215	240	280	325	360	420	480	
37" x 49"					230	250	300	350	420	470	550
					290	290	350	410	470	530	650

Capacities indicated are based on feed material weighting 1.6 T/m<sup>3</sup>, under ideal conditions of feeding & with Standard Jaw Plates.

## JAW CRUSHER TECHNICAL DETAILS

Nominal feed opening	Inch. mm.	20" x 32" 510 x 800	24" x 36" 610x910	30" x 40" 760x1000	34" x 44" 850x1100	37" x 49" 950x1250
Feed Size in./mm.		16/400	20/500	26/600	28/700	32/800
Power	H. P.	75	100	150	200	200
Speed	R. P. M.	330	270	250	220	210
Weight	Tones	9.5	16.5	24.5	28	38

(Specifications are subject to change without notice.)

## SHREE CONMIX ENGINEERS PVT. LTD.

7603, G.I.D.C. Estate, Phase-IV, Vatva, Ahmedabad - 382 445.  
 Phone : 0091 - 79 - 2584 0917, Telefax : 0091 - 79 - 2584 0297  
 E-mail : info@conmixcrusher.com Website : www.conmixcrusher.com

